


WAVEGUIDE STRAIGHT SECTIONS

SERIES
11



GENERAL INFORMATION

- FULL WAVEGUIDE FREQUENCY RANGE
- LENGTHS TO 120 INCHES
- STANDARD EXTERIOR FINISH IS FLAT BLACK POLYURETHANE ENAMEL COLOR 37038 PER FED-STD-595
- LOWER VSWR OVER NARROWER BANDS
- MULTIPLE BENDS AND CUSTOM DESIGNS AVAILABLE

SPECIFICATIONS

BASIC MODEL	FREQ. RANGE (GHz)	EIA DESIG.	VSWR (max.)	INSERT. ² LOSS (dB max.)	WT. ³ (lbs.)
11L ¹	1.12-1.7	WR650	1.05	.02 + .007 dB/ft	6.0 + 2.0 lbs/ft
11M ¹	1.7-2.6	WR430	1.05	.02 + .008 dB/ft	4.0 + 1.4 lbs/ft
11S	2.6-3.95	WR284	1.05	.01 + .009 dB/ft	3.0 + 2.9 lbs/ft
11SC	3.3-4.9	WR229	1.05	.01 + .011 dB/ft	2.5 + 2.3 lbs/ft
11C	3.95-5.85	WR187	1.05	.03 + .016 dB/ft	2.0 + 1.7 lbs/ft
11CA	4.9-7.05	WR159	1.05	.03 + .019 dB/ft	1.7 + 1.3 lbs/ft
11A	5.85-8.2	WR137	1.05	.03 + .023 dB/ft	1.5 + 1.1 lbs/ft
11XL	7.05-10	WR112	1.05	.04 + .035 dB/ft	1.1 + .92 lbs/ft
11X	8.2-12.4	WR90	1.05	.04 + .045 dB/ft	.70 + .63 lbs/ft
11XK	10-15	WR75	1.05	.05 + .060 dB/ft	.45 + .55 lbs/ft
11KU	12.4-18	WR62	1.05	.06 + .070 dB/ft	.30 + .40 lbs/ft
11K	18-26.5	WR42	1.05	.07 + .150 dB/ft	.15 + .27 lbs/ft
11KA	26.5-40	WR28	1.05	.09 + .250 dB/ft	.10 + .25 lbs/ft

Ordering Code

NOTES: 1 - available in aluminum only
2 - at worst case freq.
3 - wt. shown for copper

MODEL	FLANGE	MAT'L	FINISH	LENGTH A
FROM ABOVE	1 - CPRF 2 - CPRG 3 - COVER 4 - CHOKE 5 - SPECIAL	A - ALUM B - BRASS C - COPPER D - SPECIAL	1 - IRIDITE 2 - SILVER 3 - SPECIAL	INCHES

INTERNATIONAL TELECOMMUNICATION COMPONENTS, INC.

94B East Jefryn Blvd., Deer Park, NY 11729

(516) 243-1444

FAX (516) 595-9160

I T C